



SG BODY REFLECTOR BASE / MUTING

957951130

SG4-RDB2L

RETROREFLECTIVE TYPE 4 SAFETY LIGHT GRID FOR
BODY DETECTION

OVERVIEW

- One active and one passive unit to reduce wiring and installation costs
- Robust housing for harsh environments
- Easy installation and alignment
- Reflective muting arms included in L and T muting version
- All advanced features associated to muting function
- 2, 3, 4 beams for body protection
- Controlled heights 500, 800, 900 and 1200 mm
- Up to 8 m operating distance
- Simple configuration through DIP switches
- Integrated muting lamp (muting models)
- Anti-interference coding
- External muting enable signal
- Edged or triggered muting dependent override

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	n/a
Resolution	500mm
controlled height	500 mm
number of rays	n/a

Sensitivity adjustment	n/a
------------------------	-----

Effective Aperture Angle	$\leq \pm 2,5^\circ$
--------------------------	----------------------

Application

Function Principle	Passive side
--------------------	--------------

Available functions	Passive Unit
---------------------	--------------

Description	Big RRX passive unit L arms
-------------	-----------------------------

Functions	Body protection 2 beams muting
-----------	--------------------------------

Safety parameters

Type	Type 4 safety light curtain (A/M)
------	-----------------------------------

SIL	n/a
-----	-----

SILCL	n/a
-------	-----

PL	n/a
----	-----

PFHd	n/a
------	-----

MTTFd	n/a
-------	-----

SFF	n/a
-----	-----

Outputs

Output type	n/a
-------------	-----

Response time	n/a ms
---------------	--------

Electrical data

Operating Voltage	n/a
Load current	≤ 500mA each output
Emission	n/a
Interference to external light	According to IEC 61496-2
Power Consumption - Receiver	n/a
Power Consumption - Emitter	n/a
Cabel Length (Power Supply/Output)	n/a

Mechanical data

Dimensions	52x57x520
Connections	n/a
Storage temperature	-25...+ 70°C
Material	Painted aluminum / PMMA / PBT Valox 508
Vibrations	Width 0.35 mm, frequency 10 ... 55Hz; 20 sweep per axis, 1octave/min (EN 60068-2-6)
Shocks	16 ms (10 G) 1,000 shocks per axis (EN 60068-2-29)

Test/Approvals

EMC compatibility	According to 2014/30/EU Directive
-------------------	-----------------------------------

Generical Data

--	--

Dimensions	52x56,9x580,5 mm
Operating Temperature	0...+55°C
Humidity	15 ... 95 % (no condensation)
Mechanical Protection	IP65

**Datasensing
S.r.l.**

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
25/11/2024
20:43:22