



S5

G5210137

S5-5-F8-37
TUBULAR SENSORS

OVERVIEW

- Wide versatility of optic functions and connections
- High operating distances for all functions
- Models with trimmer adjustment and stability LED
- Rugged and impermeable plastic housing

TECHNICAL FEATURES

Detection properties

Nominal sensing distance

8m

Sensitivity adjustment

Trimmer

Application

Function Principle

Diffuse reflection (medium distance, $\leq 600\text{mm}$)

Description

Tubular M18 - radial optic

Functions	Through beam receiver
-----------	-----------------------

Outputs

Output type	NPN/PNP - Dark/Light sel.
-------------	---------------------------

Response time	2
---------------	---

Electrical data

Operating Voltage	10...30VDC
-------------------	------------

LED indicators	Green (powerON)
----------------	-----------------

Time delay before availability	≤200ms
--------------------------------	--------

Emission	n/a
----------	-----

Mechanical data

Dimensions	Ø18x84
------------	--------

Connections	M12 plug
-------------	----------

Material	Plastic ABS / PMMA
----------	--------------------

Test/Approvals

EMC compatibility	EN 60947-5-2
-------------------	--------------

Generical Data

Dimensions	Ø18x84
------------	--------

Operating Temperature	- 15°C...+ 55°C (Without freeze)
-----------------------	----------------------------------

Datasensing
S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

date of
printing

24/11/2024
08:36:37