



# S5

## G5210830

S5-5-E1-30  
TUBULAR SENSORS

## OVERVIEW

- Wide versatility of optic functions and connections
- High operating distances for all functions
- Models with trimmer adjustment and stability LED
- Rugged and impermeable plastic housing

## TECHNICAL FEATURES

### Detection properties

Nominal sensing distance	22   85mm
--------------------------	-----------

Sensitivity adjustment	Trimmer
------------------------	---------

### Application

Function Principle	Diffuse reflection (medium distance, $\leq 600\text{mm}$ )
--------------------	--

Description	Tubular M18 - axial optic
-------------	---------------------------

Functions	Optic fiber amplifier
-----------	-----------------------

#### Outputs

Output type	NPN/PNP - Dark/Light sel.
-------------	---------------------------

Response time	1
---------------	---

#### Electrical data

Operating Voltage	10...30VDC
-------------------	------------

LED indicators	Green (powerON)
----------------	-----------------

Time delay before availability	≤200ms
--------------------------------	--------

Emission	LED Red
----------	---------

#### Mechanical data

Dimensions	Ø18x82
------------	--------

Connections	2m cable
-------------	----------

Material	Plastic ABS / PMMA
----------	--------------------

#### Test/Approvals

EMC compatibility	EN 60947-5-2
-------------------	--------------

#### Generical Data

Dimensions	Ø18x82
------------	--------

Operating Temperature	- 15°C...+ 55°C (Without freeze)
-----------------------	----------------------------------

**Datasensing**  
**S.r.l.**

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail  
info@datasensing.com

**date of**  
**printing**

24/11/2024  
10:25:24