



S6

950201160

S6R-5-F20-P

MULTIVOLTAGE 50X50 MM COMPACT SENSORS SERIES

OVERVIEW

- 50x50 mm compact dimensions
- Free voltage Vac/Vdc models with relay output
- 10-30 Vdc model with transistor output
- Standard cable or M12 4-pole connection

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	20m
--------------------------	-----

Sensitivity adjustment	Trimmer
------------------------	---------

Application

Function Principle	Through beam receiver
--------------------	-----------------------

Description	Compact square case
-------------	---------------------

Functions	Through beam receiver
-----------	-----------------------

Outputs

Output type	PNP - Dark mode L/D selectable by cable/connector
Output Function	L/D selectable by cable/connector
Switching frequency	250Hz
Response time	2ms

Electrical data

Operating Voltage	10...30VDC
No-Load supply current	$\leq 30\text{mA}$
Load current	$\leq 100\text{mA}$
LED indicators	Red OUTPUT
Short-circuit protection	YES
Reverse Polarity Protection	Yes
Emission	n/a
Interference to external light	according to EN 60947-5-2 : 2020
Impulsive Overvoltage Protection	Yes
Insulation resistance	$>20\text{ M}\Omega$ 500 Vdc, between electronics and housing
Contact resistance	500 Vac 1 min., between electronics and housing

Mechanical data

Dimensions	18x50x50
------------	----------

Housing Material	ABS
Connections	M12 plug
Active Head Material	PMMA
Storage temperature	- 25°C...+70°C
Material	
Diameter/Dimension	Cubic

Test/Approvals

Approvals	CE cULus
Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)

Generical Data

Dimensions	18x50x50
Operating Temperature	- 25°C...+ 55°C (Without freeze)
Mechanical Protection	IP65

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
25/04/2025
11:27:16