



# DATAVS2

95A252790

CV-A1-32-B-03

THE RIGHT CONNECTION FOR YOUR PHOTOELECTRIC  
SENSORS FOR INDUSTRIAL ENVIRONMENT

## OVERVIEW

- M8 and M12, axial or radial female connectors
- Standard length cables: 2, 3, 5, 7, 10, 15, 25 or 50m
- 3, 4, 5, 8 or 12 poles
- Shielded or unshielded models
- P.U.R. coated models for use in harsh environments
- P.V.C. coated models for standard use
- Standard M12 4 pole non-cabled connectors
- The cable jacket maybe marked 300V only as insulation voltage between wires, the operational voltage is 24Vdc or 10-30Vdc, less than 80 V required by CCC-China

## TECHNICAL FEATURES

### Detection properties

Nominal sensing distance	n/a
Sensitivity adjustment	n/a

### Application

Function Principle	DVS2-VSM cable/conn.
Description	Straight female shielded

Functions	DVS2-VSM cable/conn.
-----------	----------------------

#### Outputs

Output type	n/a
-------------	-----

Response time	n/a
---------------	-----

#### Electrical data

Operating Voltage	n/a
-------------------	-----

Emission	n/a
----------	-----

#### Mechanical data

Dimensions	L=3m
------------	------

Housing Material	PVC (Black)
------------------	-------------

Connections	M12 plug
-------------	----------

Storage temperature	- 25°C...+70°C
---------------------	----------------

Material	
----------	--

#### Generical Data

Dimensions	L=3m
------------	------

### **Datasensing S.r.l.**

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail

### **date of printing**

10/04/2025  
23:47:24

[info@datasensing.com](mailto:info@datasensing.com)