

# SR21



953151080

## SR21-RG

2 MM HIGH-RESOLUTION FORK SENSORS FOR LABELING AND PACKAGING

## OVERVIEW

- 25 kHz high switching frequency
- IR or red/green light models
- Detection of labels (SR21-IR) or print register mark on transparent films (SR21-RG)
- 4 wire NPN and PNP output

## TECHNICAL FEATURES

### Detection properties

Nominal sensing distance	2mm
minimum detectable object	0,5mm
Sensitivity adjustment	Teach-in

### Application

Function Principle	Fork for label and color mark detection
Description	Compact - fork 2x50 mm
Functions	Fork for label and color mark detection

## Outputs

Output type	NPN/PNP L/D Selectable
Output Function	L/D Selectable
Switching frequency	25kHz
Response time	0,02

## Electrical data

Operating Voltage	10...30VDC
No-Load supply current	$\leq 55\text{mA}$
Load current	$\leq 100\text{mA}$
Output voltage drop	$\leq 2\text{V}@I_{\text{load}}=100\text{mA}$
LED indicators	Yellow (status output), Green/Red (Read/Error)
Short-circuit protection	YES
Reverse Polarity Protection	Yes
Emission	LED Red/green
Interference to external light	according to EN 60947-5-2 : 2020
Impulsive Overvoltage Protection	Yes
Insulation resistance	$>20\text{ M}\Omega$ 500 Vdc, between electronics and housing
Contact resistance	500 Vac 1 min., between electronics and housing

## Mechanical data

Dimensions	20x26x90
Housing Material	Metal - Zamak
Connections	M8 plug 4pin
Active Head Material	PMMA
Storage temperature	- 25°C...+70°C
Material	
Depth slot detection	50mm

## Test/Approvals

Approvals	CE cULus
Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)

## Generical Data

Dimensions	20x26x90
Operating Temperature	- 20°C...+ 60°C
Mechanical Protection	IP65

## **Datasensing S.r.l.**

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail

**date of  
printing**  
24/11/2024  
18:50:23

[info@datasensing.com](mailto:info@datasensing.com)